



8HDD			
Model		JF-ADVR-K7216	JF-ADVR-K7232
Video			
Encode		16CH*1080P@12fps/16CH*1080N@25fps	32CH*1080P@12fps/32*1080N@25fps
Playback		16CH*1080P@12fps/16*1080N@25fps	16CH*1080P@12fps/8*1080N@25fps
Multi-Mode	Analog	16CH*1080P/16CH*1080N	32CH*3M
	Hybrid	8CH*1080P(Analog)+8CH*1080P(IP)	8CH*1080P(Analog)+8CH*1080P(IP)
	IP	32CH*1080P/16CH*3M /8CH*5M	8CH*1080P+8CH*960P/8CH*3M /4CH*5M
Video Compression		H.264	
Audio			
Audio Compression		G.711A	
Interface			
Video Input		16*BNC	32*BNC
Video Output		1*HDMI (MAX:4K)1*VGA (MAX:1080P)	
Audio I/O		16/1	
Alarm I/O		16/4	
Ethernet		1*10/100M/1000Mbps Ethernet port, RJ45 port	
PTZ Control		1*RS485,1*RS232. Support for multiple PTZ protocol	
USB		2*USB2.0	
Max HDD		8*6TB	
General			
Temperature		0 °C - + 55 °C	
Humidity		10% -90% RH	
Power		ATX	
Consumption		<15W(Without HDD)	
Dimension		443mm(L)*427.5mm(W)*92mm(H)	