



Model No.	LI40DHTC100B	LI40DAD100V	LI40DAD100A	LI40DHTC130S	LI40DHTC130I	LI40DHTC200F	LI40DHTC200NA	LI40DHTC200NS	LI40DHTC200FV	LI40DHTC200EP	LI40DHTC200ES	LI40DHTC200ESL	LI40DHTC200AEP	LI40DHTC200AKES	LI40DHTC200AKESL	LI40DAD300NA	LI40DAD400V	
Video Output Mode	AHD/CVI/TVI/CVBS	AHD	AHD/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/TVI	AHD	
Camera																		
Image Sensor	OV9732	OV9732	AR0141	IMX225	S3130	F22	AR0237	IMX323	OV2718	MN34227	IMX323	IMX290	MN34227	IMX323	IMX290	AR0330	OV4689	
DSP	HTC960E	NVP2411H	HTC960	HTC960E	HTC960E	HTC1080E	NVP2411H	NVP2411H	HTC1080E	HTC1088	HTC1088	HTC1088	HTC1088	HTC1088	HTC1088	NVP2470H	NVP2475H	
Image Resolution	720P	720P	720P / 960H	960P / 960H	1080P / 960H	1080P	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	3MP / 960H	4MP	
Effective Pixels	1280*720	1280*720	1280*720	1280*960	1280*960	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1536	2560*1440	
TV System	PAL/NTSC																	
Electronic Shutter	1/25~1/50,000s, 1/30~1/60,000s																	
S/N Ratio	25dB																	
Scanning System	Progressive Scan																	
Lens																		
Focus Length	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm	
Focus Control	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Auto	Auto	Auto	Manual	Manual
Lens Type	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Auto	Auto	Auto	Manual	Manual
Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	3M Pixels	5M Pixels
Auto Iris Support	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	
Night Vision																		
Infrared LED	14x 30PCS																	
Infrared Distance	40M																	
IR Status	Under 10 Lux by CDS																	
IR Power On	CDS Auto Control																	
Camera Features																		
Day/Night	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	
OSD Menu Language	YES	NO	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	
White Balance	AUTO / MANUAL	AUTO	AUTO	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	
Gain Control	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	
Noise Reduction	DNR	3DNR	DNR	DNR	DNR	DNR	3DNR	3DNR	DNR	3DNR	3DNR	3DNR	3DNR	3DNR	3DNR	DNR	DNR	
Picture Adjustment	YES	NO	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	
WDR	YES	YES	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	
OSD Support	YES	NO	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	
LTC	YES	NO	NO	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	
General																		
Housing	Metal IP66																	
Bracket	YES																	
Dual Voltage	Optional																	
IR Cut Filter	YES																	
Heater	NO																	
Operation Temperature	-10°C ~ +50°C RH95% Max																	
Storage Temperature	-20°C ~ +60°C RH95% Max																	
Power Source	DC12V±10%, 700mA																	
Dimension	207(W) x 184(H) x 83(D)mm																	
Weight	1400g																	