



Model	LS-N2008HN
--------------	-------------------

System

Main Processor	ARM Cortex A9 Processor(HI3520D)
Operating System	Embedded LINUX

Video

Input	8CH (1920x1080, 1280x960, 1280x720, etc), Incoming Bandwidth: 60MB
Output	1 VGA, 1 HDMI

Alarm

Sensor Input	NO
Output	NO
Motion Detection	8 Channel
Email Alarm	Support

Display

VGA	Resolution: 800x600, 1024x768, 1280x720, 1280x1024, 1920x1080
HDMI	Resolution: 1080P(1920x1080) 720P:(1280x720)
Display Split	8 Channel/ 4 Channel / 1Channel
Digital Zoom	NO
OSD	Camera title, Time, Video loss, Recording, Motion Detection

Recording

Video Compression	H.264
Resolution	8CHx1080P/8CHx960P/8CHx720P, etc
Record Rate	PAL :1080P@200fps, 960P@200fps, 720P@200fps, D1@200fps NTSC:1080P@240fps, 960P@240fps, 720P@240fps, D1@240fps
Record Mode	Manual\Timer\Motion Detection

Playback & Backup

Local Sync Playback	1x1080P
Remote Sync Playback	YES
Search Mode	ALL, Channel, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play
Backup Mode	USB Device/Network

Network

Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
-----------	---

Network Functions	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, FTP, IP Search, P2P
Onvif Version	Support Onvif 2.4
Web Browser	IE6-11, Google Chrome (IE Tab), Firefox (IE Tab)
CMS Software	Support Windows XP / Windows Vista / Windows 7/ Windows 8
Cloud Support(P2P)	Yes
Smart Phone	iPhone, iPad, Android, Android PAD

Hard Disk Driver

Interface Type	1 SATA Interface
Capacity	Up to 6TB capacity

General

Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek
USB Interface	2 USB 2.0 Interfaces
Power Supply	DC12V/2A
Working Environment	-10~55°C/10~90%
Dimension(W×D×H)	260*190*43(mm)
Weight	2.0KG (without HDD)